

Year: 2018
Make: Chevrolet
Model: 4500 LCF Gas 2WD Reg Cab 150"
VIN: 54DCDW1B1JS810095

Engine: VORTEC 6.0L V8 SFI, GMPT-V8 8 CYLINDER V BLOCK, FOUR CYCLE OVERH..
Transmission: 6-SPEED AUTOMATIC, 6L90-E HYDRA-MATIC WITH LOCK-UP CONVE...
Exterior:
Interior: Very Dark Pewter

SAFETY

- Daytime Running Lamps
- Brake, parking, cable actuated, internal expanding drum type, transmission-mounted

INTERIOR

- Storage, seatback pockets
- Lighting, interior dome
- Storage, door pockets
- Windshield washer bottle access on passenger side dash when passenger-side door is open
- Air conditioning, single-zone manual, integral in-dash mounted
- Cruise control, electronic, automatic
- Door locks, power
- Windows, power
- Driver Information Center
- Steering column, Tilt-Wheel
- Steering wheel, urethane
- Floor mats
- Cup holders
- Seat trim, Cloth
- Seat, front high back bucket driver and passenger tricoat cloth covered reclining highback driver seat with single two occupant fold down passenger seat

ENTERTAINMENT

- Audio system feature, 2 speakers
- Audio System, AM/FM stereo with CD player, auxiliary jack, USB port and Bluetooth

EXTERIOR

- Windshield wiper, pulse, wet arm
- Mirror, outside left hand and right hand dual cab mounted exterior with integral convex mirror

- Glass, tinted
- Assist steps
- Tires, rear, 225/70R19.5 G 128/126 L BW HWY VAR1
- Tires, front, 225/70R19.5 G 128/126 L BW HWY VAR1
- Wheels, 19.5" x 6", K steel

MECHANICAL

- Exhaust, single outlet
- Fuel tank, 30 Gallon, (113L), rectangular fuel tank. mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill
- Brakes, 4-wheel antilock, front disc, rear drum, dual circuit, vacuum assisted hydraulic with EBD (Electronic Brake Distribution). Disc front and self-adjust outboard mounted drum rear. Mechanical, transmission-mounted parking brake. Non-asbestos semi-metallic linings are standard. 4 channel anti-lock brake system.
- Vehicle Application Truck
- Rear axle, 11,020 lbs. (4998 kg) R050, full-floating single-speed with oil lubricated rear wheel-bearings
- Front axle, 6,830 lbs. (3098 kg), reverse Elliot "I"-beam includes integral hydraulic power steering. ratio 18.8-20.9:1
- Rear suspension, 12,900 lbs. (5851 kg), multi-leaf, semi-elliptical steel alloy. Includes shock absorbers
- Front suspension, 8,440 lbs. (3828 kg) tapered leaf, semi-elliptical steel alloy tapered leaf springs. Includes shock absorbers and stabilizer bar.
- GVWR, 14,500 lbs. (6577 kg)
- Wheelbase, 150" (381.0 cm)
- Incomplete vehicle certification
- Frame, ladder-type channel frame. Full C section straight frame 33.5" (85.1 cm) wide. Yield strength 44,000 psi, section modulus 7.20 cu.in. and RBM 316,800 lb-ft/in per rail.
- Alternator, 145 amps output with integral regulator
- Battery, 750 cold-cranking amps, 12-volt single, maintenance free, frame-mounted battery box
- Drivetrain, rear-wheel drive
- Air cleaner, heavy-duty, 11" diameter dry paper single element. Air cleaner canister standard with air restriction gauge. Back of cab location.
- Axle, 4.30 ratio

CITY MPG

16



HIGHWAY MPG

23

Actual mileage will vary with options, driving conditions, driving habits and vehicle's condition

INSTALLED OPTIONS

[092] Axle, 4.30 Ratio	\$0
[1WT] Preferred Equipment Group	\$0
• standard equipment	
[16U] Arc White	\$0
[HNF] Very Dark Pewter, Cloth Seat Trim	\$0
[MTE] Plo, Fire Extinguisher And Safety Reflector Mounting Provisions	\$90
Original Shipping Charge	\$1,125

Get more information on your smartphone:



www.palmsautosales.com
916-560-3020