

Year: 2007
 Make: Chevrolet
 Model: CT7500 Regular Tilt Cab
 VIN: 1GBK7F1337F410450

Engine: Straight 6 Cylinder Engine
 Transmission: 5-Speed A/T
 Exterior:
 Interior: Medium Dark Gray

SAFETY

- Horn, Single electric horn mounted behind bumper. - Steering button activated.
- Exterior Lighting, Halogen headlights, daytime running lights are standard
- Side impact door beams - , 75 degree passenger door opening.
- Two lap/shoulder assemblies with three point design.
- Air Bags, Supplemental Inflatable Restraints not included
- Brake system, hydraulic split - with 4-channel ABS disc-type Bosch Hydro Max high performance booster, tandem master cylinder provides independent front and rear circuits, front and rear disc Meritor calipers: 15 3/8" rotor diameter, 1 1/2" rotor thickness with 2 1/2" diameter pistons

INTERIOR

- Seat Trim, Vinyl, Medium Dark Gray
- Interior Trim, Medium Dark Gray
- Parking Brake, Hand lever operated transmission mounted drum brake
- Radio, AM-FM stereo - with two speakers in instrument panel, antenna in "A" pillar
- Seat, Passenger, High-back bucket, Fixed height, manual back angle adjuster - and lumbar
- Seat, Driver, High-back bucket, Fixed height, manual adjuster. - back angle adjuster and lumbar
- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning
- 12 volt power supply post style
- Cigarette lighter
- Electrical/Power Outlets, 4-way hazard flasher switch, directional, high/low switch and flash to pass. - LH column switch.
- Vinyl floor covering with insulation.
- Dual ashtrays, door mounted
- Door panels are dark gray with integral armrests.
- Dark gray padded instrument panel.
- Two over head shelves with doors - , storage tray adjacent to driver, optional center seat with cup holder.
- Warning Lights-inc: High beams, Check gauges, Brake, Low coolant, Seat belt, Battery, Reduced engine power, Low air, Change oil, Low oil level, Service engine soon, Engine shutdown, Daytime running lamps, Engine overspeed, Left turn signal, Right turn signal, Antilock
- Gauges-inc: Fuel, Volt, Coolant temperature, Oil pressure, Speedometer, Odometer/trip odometer/hour meter, Tachometer
- Right hand coat hook.
- Padded vinyl driver and passenger sunshades
- Three point entry system. - Two front grab handles and one rear.
- Steering wheel is soft touch, 18.9" diameter
- Steering, Power - ZF variable ratio power
- Steering, Tilt and telescopic steering column.
- Interior Lighting, Dome lamp is activated by left hand door switch also by Dome lamp switch
- Heating and Air Conditioning, Heater/power ventilator/defroster.

EXTERIOR

- Paint Scheme, Solid
- Mirrors, Outside passenger side and driver side, West Coast stainless steel heads and brackets, dual 7" x 16". - Set for 102" body width.
- 89 inch effective BBC - , 2 step entry, wheel well splash guards, inner and outer fenders, extended corrosion treatment
- Tilt up panel for service access to washer motor and washer fluid and cab fresh air filter - , inside lower dash release.
- Horn, Single electric horn mounted behind bumper. - Steering button activated.
- Passenger door lower glass -

- Electric two-speed and adjustable intermittent wipers include wet arm windshield washer.
- Tempered tinted side glass window - with driver side manual crank window
- Windows, The windshield is laminated tinted glass and is bonded to improve occupant protection.
- Side impact door beams - , 75 degree passenger door opening.
- Cab Mounts, Cylindrical rubber mounts at front and rear. - Cab tilt lock RH side.
- Exterior Lighting, Five roof mounted clearance lamps and headlamps are controlled via the LH column mounted switch for truck application or with a dash mounted switch for tractor applications.
- Exterior Lighting, Halogen headlights, daytime running lights are standard
- Full width bumper. - A plastic fascia is supported by a steel beam.

MECHANICAL

- Brake system, hydraulic split - with 4-channel ABS disc-type Bosch Hydro Max high performance booster, tandem master cylinder provides independent front and rear circuits, front and rear disc Meritor calipers: 15 3/8" rotor diameter, 1 1/2" rotor thickness with 2 1/2" diameter pistons
- Fuel Tank, Single, 50 gallon fuel capacity, driver side only - and a green fuel cap
- Frames, Rail, painted semi-gloss Black 8mm - 80,000 psi yield strength, steel frame, SAE J1392-080XLK steel, dimensions 10" outside diameter x 3.2" flange x 5/16" thickness, section modulus 12.69 cu. in., RBM 1,015,000
- Wheelbase, 128" - with 97" CA
- Rear Tread, Premium highway
- Rear Manufacturer Code - Goodyear
- Rear Tires, 245/75R22.5G - 17,200 lbs. capacity,
- Rear Wheels, 22.5" x 7.5", steel disc - Accuride 10-hole, flange nut, hub piloted, 11.25" bolt circle, painted Gray 26,440 lbs. capacity,
- Rear Suspension, Rear Multi-Leaf, 19,000 lbs. capacity
- Rear Axle Ratio, 4.88:1
- Rear wheel drive
- Rear Axle, Single Speed, Dana 19060S, 19,000 lbs. capacity - includes 75W-90 synthetic lubricant and National brand oil seals
- Front Tread, Premium, highway
- Front Manufacturer Code - Goodyear
- Front Tires, 245/75R22.5G-9350 lbs. capacity,
- Front Wheels, 22.5" x 7.5", steel disc - Accuride 10-hole, flange nut, hub piloted, 11.25" bolt circle, painted Gray , 13,220 lbs. capacity,
- Front Stabilizer bar - solid bar style
- Front Suspension, Front Tapered Leaf, 10,000 lbs. capacity
- Front Axle, 10,000 lbs. capacity - Up to 53 degree turn angle
- TranSynd synthetic automatic transmission fluid
- Automatic Transmission, Allison 2500 5-speed - with 4th Generation Electronic Controls with 0.74 over drive. Torque rating: 550 lb-ft, 33,000 lbs. maximum GVWR/GCWR. Includes transmission oil cooler in radiator, and floor mounted "T" handle shifter With Option PTX, the truck will be equipped with the Allison 2500 HS Highway Series transmission. When ordered with option PTO, the truck will be equipped with the Allison 2500 RDS Rugged Duty Series transmission.
- Option PTO not required - This option should only be ordered when a customer specifically does not require an electric hand throttle for use with power-take-off provisions.
- Exhaust System, Single horizontal exhaust system. - passenger side mounted inside frame rail, aluminized steel
- Battery, Dual, 750 CCA, Delphi Heavy-Duty Freedom BS 31-750 12V - 320-minute reserve capacity @ 27 degrees C, 750 CCA @ -18 degrees C
- Alternator, 22SI, Delco 100-amp maximum
- Fuel Water Separator, Racor frame-mounted spin-on type with sight bowl, drain, and paper element. Includes water-in-fuel telltale dash light - Standard with Isuzu diesel engines includes 150 watt heater.
- Road Speed Governor, controlled by the speed rating of the tires ordered. All vehicles with 19.5" tire sizes and with most 22.5" have speed governed to a maximum of 75 mph. A few aggressive tire tread patterns may have lower maximum speed ratings that limit governed speed to 65 or 55 mph - see tire company specifications for details.
- Air Cleaner, Dry-type standard filter element
- Truck Application NOTE: Federal Excise Tax of 12% must be paid on the final selling price for trucks with GVWR's of 33,001 lbs. and above.

CITY MPG

17



HIGHWAY MPG

24

Actual mileage will vary with options, driving conditions, driving habits and vehicle's condition

New

MSRP	\$63,266.00
INSTALLED OPTIONS	
[GZ1] Rates GVWR At 25,950 LBS. (11,770 KG) Capacity	\$0
[JE4] Abs 4 Channel Bendix Brake System 'S' Cam Type Meritor	\$2,244
[LG4] Pre 2007i Emission Isuzu Diesel Engine	-\$7,561
[YF5] California State Requirements	\$0
[K40] Butterfly Valve Type	\$492
[NPE] Electronic Exhaust Restrictor (Automatic)	\$406
[N8] 100 Gallon (380 L) Total Fuel Capacity	\$370
[JRF] Rear Dust Shields	\$0
[KK3] Haldex 292 Water Cooled 12.9 CFM	\$725
[KVG] Air Intake Compressor	\$0
[V01] Heavy Duty Increased Cooling Capacity Radiator	\$0
[C60] Air Conditioning	\$939
[KBB] 1250 Watt, 110 V	\$50
[PTO] Electronic Activation Switch, (Electric Hand Throttle), Ip Mounted	\$215
[MTX] Allison 2200 Series (Close Ratio) 5 Speed	\$405
[MBT] Transynd Synthetic Automatic Transmission Fluid	\$0
[0F1] Front Oil Seals With Clear Caps	\$21
[009] 5.29:1	\$0
[GN8] Rear Multi Leaf 21,000 LBS. (9525 KG) Capacity	\$20
[G60] Single Tapered Leaf, Not Rated	\$88
[GN1] Rear Stabilizer Bar	\$177
[EV9] Bolted Rear Suspension	\$21
[EL5] 212" (538.4 CM)	\$711
[AQT] Air Suspension, High Back	\$200
[AV8] Center Passenger Seat	\$182
[K34] Cruise Control	\$52
[C] Ioth, Medium Dark Gray	\$40
[DTF] Spot Mirrors, Outside Passenger Side And Driver Side, 8" Stainless Steel	\$26
[U08] Dual Note, Electric	\$21
[UZF] 97 Decibels, Electrical	\$102
[UM6] Am FM Stereo Radio/Cassette	\$165
[RPO] 22.5" X 8.25" (58.9 CM X 21 CM), Steel Disc Accuride 10 Hole, Flange Nut, Hub Piloted	\$0
[RRR] 22.5" X 8.25" (58.9 CM X 21 CM), Steel Disc Accuride 10 Hole, Flange Nut, Hub Piloted	\$0
[XRN] 295/75 R22.5 G 12,350 LBS. (5602 KG) Capacity	\$230
[YRN] 295/75 R22.5 G 22,700 LBS. (10,300 KG) Capacity	\$460
[40P] White Powder Coated Painted Wheels	\$50
Original Shipping Charge	\$1,250
RETAIL PRICE (ORIGINALLY NEW)	\$65,367.00

CARCONNECTION
Superstore

www.carconnection1.com/
 724-658-1212