Year: 2005
Make: Chevrolet
Model: CT6500 Regular Tilt Cab
VIN: 1GBJ6F1395F529664

Engine: Straight 6 Cylinder Engine
Transmission: 6-Speed M/T
Exterior: White (16U)
Interior: Medium Dark Gray

MECHANICAL

· Truck Application
· Air Cleaner, Dry-type standard filter element
· Road Speed Governor, controlled by the speed rating of the tires ordered. All vehicles with 19.5" tire sizes and with most 22.5" and 24.5" tires have speed governed to a maximum of 75 mph . A few aggressive tire tread patterns may have lower maximum speed ratings that limit governed speed to 65 or 55 mph - see tire company specifications for details.
· Fuel/Water Separator, Racor frame-mounted spin-on type with sight bowl, drain and paper element. includes water-in-fuel telltale dash light - Standard with Duramax diesel engines includes 150 watt heater. Optional with Caterpillar diesel engines filter will be non-heated type.
· Alternator, 22SI, 100-amp maximum
· Battery, Dual, 750 CCA, Delphi Heavy-Duty Freedom BS 31-750 12V - 320-minute reserve capacity @ 27 degrees C, 750 CCA @ -18 degrees C
· Exhaust System, Single horizontal exhaust system. - passenger side mounted inside frame rail, aluminized steel
· Option PTO not required - This option should only be ordered when a customer specifically does not require an electric hand throttle for use with power-take-off provisions.
· Automatic Transmission, Allison 2500 5-speed -with 0.74 over drive. Torque rating: 550 lb-ft, 33,000 lbs. maximum GVWR/GCWR. Includes transmission oil cooler in radiator, and floor mounted "T" handle shifter With Option PTX, the truck will be equipped with the Allison 2500HS Highway Series transmission. When ordered with option PTO, the truck will be equipped with the Allison 2500RDS Rugged Duty Series transmission,
· Front Axle, 10,000 lbs. capacity - Up to 53 degree turn angle
· Front Suspension, Front Tapered Leaf, 10,000 lbs. capacity
· Front Stabilizer bar - solid bar style
· Front Wheels, 22.5" x 7.5" , steel disc - Accuride 10-hole, flange nut, hub piloted, 11.25" bolt circle, painted Gray , 13,220 lbs. capacity,
· Front Tires, 245/75R22.5G-9350 lbs. capacity,
· Front Manufacturer Code - Goodyear
· Front Tread, Premium, highway
· Rear Axle, Single Speed, Dana S150-S 15,000 lbs. capacity -40,000 lbs. GCWR
· Rear wheel drive
· Rear Axle Ratio, 6.50:1
· Rear Suspension, Rear Multi-Leaf, 15,000 lbs. capacity
· Rear Wheels, 22.5" x 7.5" , steel disc - Accuride 10-hole, flange nut, hub piloted, 11.25" bolt circle, painted Gray 26,440 lbs. capacity
· Rear Tires, 245/75R22.5G-17,200 lbs. capacity,
· Rear Manufacturer Code - Goodyear
· Rear Tread, Premium highway
· Wheelbase, 128" - with 97" CA
· Frames, Rail, painted semi-gloss Black 8mm - 80,000 psi yield strength, steel frame, SAE J1392-080XLK steel, dimensions 10" outside diameter x 3.2" flange x 5/16" thickness, section modulus 12.69 cu. in., RBM 1,015,000
· Fuel Tank, Single, 50 gallon fuel capacity, driver side only
· Hydraulic Split brake system - with 4-channel ABS disc-type Bosch Hydro Max high performance booster, tandem master cylinder provides independent front and rear circuits, front and rear disc Meritor calipers: 15 3/8" rotor diameter, 1 1/2" rotor thickness with 2 1/2" diameter pistons

EXTERIOR

· Full width bumper. - A plastic fascia is supported by a steel beam.
· Exterior Lighting, Five roof mounted clearance lamps and headlamps are controlled via the LH column mounted switch for truck application or with a dash mounted switch for tractor applications.
· Exterior Lighting, Halogen headlights, daytime running lights are standard
· Cab Mounts, Cylindrical rubber mounts at front and rear. - Cab tilt lock RH side.
· Side impact door beams - , 75 degree passenger door opening.
· Windows, The windshield is laminated tinted glass and is bonded to improve occupant protection.
· Tempered tinted side glass window - with driver side manual crank window, excludes lower visibility window.
· Passenger door lower glass -
· Horns, Single electric horn mounted behind bumper. - Steering button activated.
· Electric two-speed and adjustable intermittent wipers include wet arm windshield washer.
· Tilt up panel for service access to washer motor and washer fluid - , inside lower dash release.
· 89 inch effective BBC - , 2 step entry, wheel well splash guards, inner and outer fenders, extended corrosion treatment
· Mirrors, Outside passenger side and driver side, West Coast stainless steel heads and brackets, dual 7" x 16". - Set for 102" body width.
· Paint Scheme, Solid

INTERIOR

· Heating and Air Conditioning, Heater/power ventilator/defroster.
· Interior Lighting, Dome lamp is activated by left hand door switch also by Dome lamp switch
· Steering, Tilt and telescopic steering column.
· Steering, Power - ZF variable ratio power
· Steering wheel is soft touch, 18.9" diameter.
· Three point entry system. - Two front grab handles and one rear.
· Dark gray padded instrument panel.
· Door panels are dark gray with integral armrests.
· Dual ashtrays, door mounted
· Right hand coat hook.
· Padded vinyl driver and passenger sunshades
· Gauges-inc: Fuel, Volt, Coolant temperature, Oil pressure, Speedometer, Odometer/trip odometer/hour meter, Tachometer
· Warning Lights-inc: High beams, Check gauges, Brake, Low coolant, Seat belt, Battery, Reduced engine power, Low air, Change oil, Low oil level, Service engine soon, Engine shutdown, Daytime running lamps, Engine overspeed, Left turn signal, Right turn signal, Antilock
· Two over head shelves with doors- , storage tray adjacent to driver, optional center seat with cup holder.
· Vinyl floor covering with insulation.
· Electrical/Power outlets, 4-way hazard flasher switch, directional, high/low switch and flash to pass. - LH column switch
· Cigarette lighter
· 12 volt power supply post style
· Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning
· Seats, Driver,High-back bucket, Fixed height, manual adjuster, - back angle adjuster and lumbar
· Seats, Passenger, High-back bucket, Fixed height, manual back angle adjuster - and lumbar
· Radio, AM-FM stereo - with two speakers in instrument panel, antenna in "A" pillar
· Standard Parking Brake, Hand lever operated transmission mounted drum brake
· Interior Trim, Medium Dark Gray
· Seat Trim, Vinyl, Medium Dark Gray

SAFETY

· Hydraulic Split brake system - with 4-channel ABS disc-type Bosch Hydro Max high performance booster, tandem master cylinder provides independent front and rear circuits, front and rear disc Meritor calipers: 15 3/8" rotor diameter, 1 1/2" rotor thickness with 2 1/2" diameter pistons
· Air bags, Supplemental Inflatable Restraints not included
· Two lap/shoulder assemblies with three point design.
· Side impact door beams - , 75 degree passenger door opening.
· Exterior Lighting, Halogen headlights, daytime running lights are standard
· Horn, Single electric horn mounted behind bumper. - Steering button activated.

CITY MPG 16

Fuel Economy Information

HIGHWAY MPG 26

Actual mileage will vary with options, driving conditions, driving habits and vehicle's condition

INSTALLED OPTIONS

[GZI] Rates GVWR At 25,950 LBS. (11,770 KG) Capacity	$0
[YF5] California State Requirements	$0
[K40] Butterfly Valve Type	$492
[NPE] Electronic Exhaust Restrictor (Automatic)	$406
[NJ8] 100 Gallon (380 L) Total Fuel Capacity	$370
[K16] Electric, Self Contained, 12 V	$153
[V01] Heavy Duty Increased Cooling Capacity Radiator	$0
[C60] Air Conditioning	$939
[KB3] 1250 Watt, 110 V	$51
[PTO] Electronic Activation Switch, (Electric Hand Throttle), Ip Mounted	$215
[MM7] Eaton Fuller FS5406 A, 6 Speed Direct Drive. Torque Rating: 560 LB FT	-$3,670
[MPK] Eaton 'Solo' Two Plate, 14" Self Adjusting	$160
[FF1] Oil Lubricated "Synthetic" Front Wheel Hubs With Clear Caps	$21
[HPK] Dana 19060 S, 19,000 LBS. (8618 KG) Capacity	$203
[090] 3.08:1	$0
[GN0] Multi Leaf, 19,000 LBS. (8618 KG) Capacity	$41
[G60] Single Tapered Leaf, Not Rated	$88
[GN1] Rear Stabilizer Bar	$177
[EV9] Bolted Rear Suspension	$21
[EK8] 188" (477.5 CM)	$558
[AQT] Air Suspension, High Back	$163
[AV8] Center Passenger Seat	$182
[K34] Cruise Control	$52
[C] loth, Medium Dark Gray	$40
[DTF] Spot Mirrors, Outside Passenger Side And Driver Side, 8" Stainless Steel	$26
[U08] Dual Note, Electric	$21
[UZF] 97 Decibels, Electrical	$102
[UM6] Am FM Stereo Radio/Cassette	$165
[Q82] 19.5" X 6.75" (49.5 CM X 17.1 CM), Steel Disc 8 Hole, Accuride, Hub Piloted	$41
[Q83] 19.5" X 6.75" (49.5 CM X 17.1 CM), Steel Disc 8 Hole, Accuride, Hub Piloted	$82
[XNC] 245/70 R19.5 H 9880 LBS. (4481 KG) Capacity	$52
[R4L] Michelin	$80
[R3B] Extra Strength, Highway	$0
[YNC] 245/70 R19.5 H 18,700 LBS. (8482 KG) Capacity	$252
[S4L] Michelin	$160
[S3B] Extra Strength, Highway	$0
[40P] White Powder Coated Painted Wheels	$50
Original Shipping Charge	$995

JAMIE JAMES
MOTOR COMPANY LLC.

www.jamiejamesmotorcompany.com
843-582-6100