

Year: 2007
Make: GMC
Model: TC7500 Regular Cab
VIN: 1GDJ7C1397F402225

Engine: Straight 6 Cylinder Engine
Transmission: 5-Speed A/T
Exterior: Summit White (50U)
Interior: Very Dark Pewter

MECHANICAL

- Truck application NOTE: Federal Excise Tax of 12% must be paid on the final selling price for trucks with GVWR's of 33,001 lbs. and above. Trucks that are used primarily to tow a trailer may be liable to Federal Excise Tax - check with IRS for guidelines. PLEASE NOTE: The 12% FET tax is NOT included in AutoBook Pricing.
- Air cleaner, dry-type standard filter element
- Underhood air cleaner restriction gauge
- Road Speed Governor, controlled by the speed rating of the tires ordered. All vehicles with 19.5" tire sizes and with most 22.5" and 24.5" tires have speed governed to a maximum of 75 mph . A few aggressive tire tread patterns may have lower maximum speed ratings that limit governed speed to 65 or 55 mph - see tire company specifications for details.
- Alternator, AD244, Delco-Remy 150-amp maximum
- Battery, single, 600 CCA, Delphi Freedom 12V. - 115-minute reserve capacity @ 27 degrees C, 600 CCA @ -18 degrees C,
- Exhaust system, single horizontal - driver side mounted inside frame rail, With Gasoline engines, stainless-steel exhaust. With diesel engines, aluminumized steel exhaust, oxidation catalyst, diesel particulate filter and exhaust gas cooler.
- Option PTO not required - This option should only be ordered when a customer specifically does not require an electric hand throttle for use with power-take-off provisions.
- TranSynd synthetic automatic transmission fluid
- Front axle, 10,000 lbs. capacity - Up to 53 degree turn angle
- Front suspension, tapered leaf, 10,000 lbs. capacity
- Front shock absorber, diameter 1.375"
- Front wheels, 22.5" x 7.5", steel disc - Accuride 10-hole, flange nut, hub piloted, 11.25" bolt circle, painted Gray , 13,220 lbs. capacity,
- Front tire size, 245/75R22.5G - 9350 lbs. capacity,
- Front tire manufacturer code, Goodyear
- Front tire tread, premium highway
- Rear axle, single-speed, Dana 19060S, 19,000 lbs. capacity - includes 75W-90 synthetic lubricant and National brand oil seals
- Rear wheel drive
- Rear axle ratio, 7.17:1
- Rear suspension, multi-leaf, 19,000 lbs. capacity
- Rear wheels, 22.5" x 7.5", steel disc - Accuride 10-hole, flange nut, hub piloted, 11.25" bolt circle, painted Gray 26,440 lbs. capacity,
- Rear tire size, 245/75R22.5G - 17,640 lbs. capacity
- Rear tire manufacturer code, Goodyear
- Rear tire tread, premium highway
- Wheelbase, 140" - with 72" CA and 135.3" CE.
- Frame, painted semi-gloss black 6mm rail - 50,000 psi yield strength, steel frame, SAE J1392-050XLK steel, dimensions 9 1/2" x 3" x 1/4" section modulus 9.58 cu. in., RBM 479,000
- Fuel tank, single, 50-gallon fuel capacity - driver side, steel top tread plate, sump, drain and steps under cab on front passenger side. Provides clean back of cab and a black tethered fuel cap with gasoline engines, and a brass tethered fuel cap with diesel engines
- Brake system, hydraulic, split - with 4-channel ABS disc-type Bosch Hydro Max high performance booster, tandem master cylinder provides independent front and rear circuits, front and rear disc Meritor calipers: 15 3/8" rotor diameter, 1 1/2" rotor thickness with 2 1/2" diameter pistons with 8,000 lb. front axle, diameter pistons with 10,000 lb. front axle
- Parking brake, hand lever operated transmission mounted drum brake

EXTERIOR

- Bumpers, front steel, painted argent - Bumper thickness 3.9 mm
- Windows, Solar-Ray tinted - all windows
- Horn, single electric mounted inside engine compartment

- Positive door stops
- Exterior roof drip moldings
- Roof marker lamps
- Front mud flaps
- Provisions for mounting front license plate
- Integral grille and fenders - The grille is the same color as hood with single halogen headlamps.
- Entry steps under cab doors are based upon fuel tank type
- Windshield wipers, 2-speed and intermittent, with pulse washers
- Daytime running lamps
- Mirror, manual, 102" wide load, integral arm, integral convex mirror - black molded composite 12" x 7" with 6" x 7" convex section
- Paint, solid, upper color, Summit White
- Paint, solid, lower color, Summit White

INTERIOR

- Stepwell storage areas at each door. Includes storage cover
- Molded vinyl floor covering
- Vinyl door trim panels - with storage pockets, beverage holders, and reflectors
- Two sided single common key for doors and ignition
- Headlamp warning buzzer
- Sunshades, passenger side and driver side, vinyl-covered
- Tachometer with automatic and manual transmissions
- Electronic engine hour meter
- Steering, power - ZF variable ratio power
- Gauges, low oil pressure and coolant level, high coolant and engine oil temperature
- Powerpoints - two in-cab power sources for electrical plug-in accessories
- Underhood bodybuilder connections accessory power supply - Provides 12V power supply from the battery with two separate 30 amp fused circuits
- Air conditioning not desired - this option should be ordered only when a customer does not require air conditioning
- Seat, driver, high-back bucket, Fixed height, manual adjuster - storage in the seat riser with a small lip at the front to help prevent contents from sliding out.
- Seat, passenger, high-back bucket, Fixed height, manual back angle adjuster - storage in the seat riser with a small lip at the front to stop contents from sliding out
- Provisions for stereo - Includes AM/FM antenna, lead wiring for speakers, and separate door chime module
- Interior trim, Very Dark Pewter
- Seat trim, vinyl, Very Dark Pewter

SAFETY

- Brake system, hydraulic, split - with 4-channel ABS
- Air bags, Supplemental Inflatable Restraints not included
- Daytime running lamps

CITY MPG

14



HIGHWAY MPG

20

Actual mileage will vary with options, driving conditions, driving habits and vehicle's condition

New

MSRP	\$45,590.00
INSTALLED OPTIONS	
[GZ1] Rates GVWR At 25,950 LBS. (11,736 KG) Capacity	\$0
[FE9] Federal Requirements	\$0
[LG4] Pre 2007 I Emission Isuzu Diesel Engine	-\$900
[LPU1] Isuzu Diesel 6 H 7.8 L I6, 215 HP (160 KW) @ 2200 RPM And 520 LB FT Torque (705 N M) @ 1450 RPM	\$10,750
[KNB] DRY Type Standard Filter Element	\$0
[NWB] Racor Frame Mounted Spin On Type	\$16
[KRW] Silicone Radiator Hoses	\$73
[KB3] 1250 Watt, 110 V	\$50
[KYR] 65 MPH (105 KPH) Speed Governor	\$0
[K60] 22 Si, Delco 100 Amp Maximum	\$0
[TNL] Dual, 750 Cca, Delphi Heavy Duty Freedom BS 31 750 12 V	\$163
[KPJ] Automatic Engine Shutdown With Alarm Is Standard	\$141
[PTO] Electronic Activation Switch, (Electric Hand Throttle), Ip Mounted	\$215
[MTX] Allison 2200 Series (Close Ratio) 5 Speed	\$405
[FF1] Front Oil Seals With Clear Caps	\$21
[F25] Multi Leaf, 12,000 LBS. (5443 KG) Capacity	\$25
[F59] Stabilizer Bar	\$141
[RPQ] 22.5" X 8.25" (58.9 CM X 21 CM), Steel Disc	\$0
[XWL] 11 R22.5 G 12,350 LBS. (5602 KG) Capacity	\$320
[009] 5.29:1	\$0
[GP1] Multi Leaf, 23,500 LBS. (10,660 KG) Capacity	\$41
[G68] Rear Shock Absorbers	\$58
[GN1] Rear Stabilizer Bar	\$177
[EV9] Bolted Rear Suspension	\$21
[RPR] 22.5" X 8.25" (58.9 CM X 21 CM), Steel Disc	\$0
[YWL] 11 R22.5 G 23,000 LBS. (10,430 KG) Capacity	\$680
[EK7] 260" (660.4 CM)	\$863
[FD5] Rail, Painted Semi Gloss Black 8 MM 80,000 Psi (551,600 Kpa) Yield Strength	\$155
[F08] Inverted "L" 80,000 Psi (551,600 Kpa) Yield Strength.	\$235
[NXN] Fuel Additional 15 Gallons (56.7 L) Fuel	\$60
[V76] Front Tow Hooks, Frame Mounted	\$51
[U08] Dual Note, Electric	\$21
[ZQ3] Driver Convenience Package	\$223
[N33] Tilt Wheel Adjustable Steering	\$173
[K34] Cruise Control	\$52
[C60] Air Conditioning	\$939
[A58] Two Person, Storage Under Fold Up Seat And In Center Seat Back	\$220
[UM7] Delco Am FM Stereo Radio	\$135
Original Shipping Charge	\$1,250
RETAIL PRICE (ORIGINALLY NEW)	\$62,364.00



www.gmotorcars.com
847-228-1900